

Assembly and Fitting Instructions

Installation should only be performed by a suitably skilled person.

Part numbers DSG040

Updated – JAN 2020

Step 1

Fit Front Mounting Bracket to a suitable position on the trailer drawbar using the U Bolt M12 x 75 x 110 or U Bolt M12 x 75 x 150 depending on chassis thickness

Warning:- Ensure any cables running along or under the chassis are not interred with



Step 2

Fit Outer Mounting Plates to each end of the Front Mounting Bracket using the M12 x 25 Bolts, Spring Washer and nuts. Do not tighten at this stage as these may need adjusting in or out during the assembly process.



Step 3

Fit Rear Mounting Bracket to trailer chassis using the Square U bolt M10 x 40 x 175 and Lower Mounting Plate.

Warning:- Ensure any cables running along or under the chassis are not interred with



Step 4

Fit Lower Tube to Front Mounting Bracket using the Small Round U Bolt M10 x 42. Top of the tube should be positioned in line with the slot in the mounting bracket plate.

Adjust position of Rear Mounting Bracket if required. Fit Lower Tube to Rear Mounting Bracket using the Small Round U Bolt M10 x 42.



Step 5

Slide the Front Support Tube RH into the end of the Lower Tube and secure to Front Mounting Bracket with a Small Round U Bolt M10 x 42.



Step 6

Slide the Upper Rear Tube RH into the end of the Front Support Tube RH using the RIGHT "A" labels as a guide.



Step 7

Slide the Rear Mounting Tube into the Lower Tube and end of Upper Rear Tube (RIGHT "B").

Secure to Rear Mounting Bracket with a Small Round U Bolt M10 x 42.

Step 8

Attach the Mesh using the bungee cords.



Step 9

Attach the Front Cross Brace Assembly to the Front Support Tube RH & LH using 2 off the Small Round U Bolts M10 x 42 .

By removing the stainless bolts the width of the Front Cross Brace can be adjusted to suit the required gap.



Secure all Fasteners



PERIODICALLY CHECK TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

JGC Components Pty Ltd, warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, JGC Components Pty Ltd, may repair or replace the product, at their opinion, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. JGC Components Pty Ltd's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.